



PEAK ANTI-SEIZE COMPOUND

COPPER & GRAPHITE GREASE NLGI 2

DESCRIPTION & APPLICATION:

PEAK ANTI-SEIZE COMPOUND is a premium, anti-seize Copper/Graphite grease designed to provide protection against corrosion and metal-to-metal contact in a wide range of automotive, marine, industrial, workshop and domestic applications, particularly where very high temperatures are encountered. It is effective up to 800°C due to the high Copper content.

PEAK ANTI-SEIZE COMPOUND can be used for thread coating/lubricant for industrial ovens, furnaces and boilers. Gasket coating for automotive, marine and industrial cylinders, manifolds and exhaust systems. Tool and drilling operations e.g. mining and oil exploration. Feed and adjusting screws, linkages and drive chains on earth moving and agricultural equipment. Screws, nuts & bolts, hinges plus car & motorcycle parts.

BENEFITS:

- High Temperature Stability and Corrosion Protection
- Excellent resistance to water washout
- Remains effective in harsh acid, alkaline and salt conditions
- Outstanding storage stability
- Corrosion preventative for acidic, alkaline or saline operating conditions
- Used for a variety of anti-seize applications

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXASC02.5	2.5 KG	6

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	2
Soap/Thickener Type	Bentone
Dropping point °C	Non- Melt
Oil Viscosity 40°C cSt	460
4 Ball Weld Load, Kg	620
Colour	Deep Copper

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 2 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982