



PEAK ROCK DRILL 150

PREMIUM MINERAL ROCK DRILL OIL

DESCRIPTION & APPLICATION:

PEAK ROCK DRILL 150 is specially formulated for the lubrication of percussion type air tools, including rock drills, paving breakers, pneumatic pile drivers, ballast tampers, chipping hammers, etc.

PEAK ROCK DRILL 150 contains advanced Extreme Pressure (EP) and Tackiness additives ensuring that equipment wear due to high speeds and heavy or shock loads is minimised.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil and equipment life
- Resists water washout by partly emulsifying with water to form a strong tacky lubricating film which delivers excellent wear protection.
- Extreme pressure additives to assist in carrying the heavy loads at the tool head.
- Additional tack which ensures strong adhesion to drill surfaces
- Excellent resistance to foaming ensuring that the oil feed will be uniform and easily controlled

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.890
Viscosity @ 40°C cSt	ASTM D7042	145
Viscosity @ 100°C cSt	ASTM D7042	15.1
Viscosity Index	ASTM D2270	105
Flash Point °C	ASTM D92	>200

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIRD150020	20 Litre	
PKIRD150205	205 Litre	
PKIRD1501000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 150 Viscosity
- ✓ DIN 51517 Part 3

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 28 June 2022

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982