



PEAK ROCK DRILL 100

PREMIUM MINERAL ROCK DRILL OIL

DESCRIPTION & APPLICATION:

PEAK ROCK DRILL 100 is specially formulated for the lubrication of percussion type air tools, including rock drills, paving breakers, pneumatic pile drivers, ballast tampers, chipping hammers, etc.

PEAK ROCK DRILL 100 contains advanced Extreme Pressure (EP) and Tackiness additives ensuring that equipment wear due to high speeds and heavy or shock loads is minimised.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil and equipment life
- Resists water washout by partly emulsifying with water to form a strong tacky lubricating film which delivers excellent wear protection.
- Extreme pressure additives to assist in carrying the heavy loads at the tool head.
- Additional tack which ensures strong adhesion to drill surfaces
- Excellent resistance to foaming ensuring that the oil feed will be uniform and easily controlled

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.878
Viscosity @ 40°C cSt	ASTM D7042	106
Viscosity @ 100°C cSt	ASTM D7042	11.3
Viscosity Index	ASTM D2270	105
Flash Point °C	ASTM D92	>200

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIRD100020	20 Litre	
PKIRD100205	205 Litre	
PKIRD1001000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 100 Viscosity
- ✓ DIN 51517 Part 3

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 5 October 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982