

PEAK MP BENTONITE GREASE 3

BENTONITE CLAY GREASE NLGI 3

DESCRIPTION & APPLICATION:

Peak MP Bentonite Grease 3 is a high quality, multipurpose high temperature clay thickened grease formulated to perform in a wide variety of applications where very high temperatures are encountered. Peak MP Bentonite Grease 3 is based on premium quality, high viscosity base oils to provide exceptional resistance to oxidation at high temperatures, good water resistance and anti-wear performance under high loads and low speeds.

Peak MP Bentonite Grease 3 is designed to meet the demands of the most hostile grease applications and conditions. Due to the inertness of the clay thickener it can be employed in harsh acid and alkaline environments, also recommended for the lubrication of automotive bearings particularly braking systems plus plain and antifriction bearings in such applications as oven conveyors or kiln bearings.

BENEFITS:

- Excellent thermal and mechanical stability over a wide temperature range
- High load carrying capacity which protects equipment against loading.
- Excellent water resistance to water spray & washout.
- Excellent anti-wear properties resulting in reduced bearing component wear.
- Reduced oil separation with a strong resistance to hardening.
- Provides superior protection against rust and corrosion

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	3
Soap/Thickener Type	Inorganic Clay
Dropping point °C	Non-Melt
Oil Viscosity 40°C cSt	460
4 Ball Weld Load, Kg	150
Operating Temperature Range °C	0 to 190
Colour	Dark Amber

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXMP3B020	20 KG	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 8 February 2021 *Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



