



PEAK CVT FLUID

FULL SYNTHETIC CVT FLUID

DESCRIPTION & APPLICATION:

PEAK CVT Fluid is formulated using synthetic base oil technology and a premium quality additive package to produce a high performance Continuously Variable Transmission (CVT) fluid.

PEAK CVT Fluid is designed for use in passenger cars, 4WD's and light commercial vehicles fitted with a CVT. It is suitable for use in Toyota, Nissan, BMW, Volkswagen and many other vehicles fitted with a continuously variable transmission.

BENEFITS:

- Excellent foam and wear properties to deliver superb performance and protection
- Strong Oxidation Performance for better resistance to oil thickening and oxidation.
- Superior Anti-Shudder Durability.
- Very high shear stability resulting in enhanced load carrying ability.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.8
Viscosity 40°C cSt	35.1
Viscosity 100°C cSt	7.1
Viscosity Index	168
Flash Point °C	>210
Colour	Amber

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKTFMCV004	4 Litre	4
PKTFMCV010	10 Litre	
PKTFMCV020	20 Litre	
PKTFMCV060	60 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL: (Suitable for Use)

- ✓ Audi/VW TL 52180 / G 052 180
- ✓ Ford WSS-M2C933-A / MERCON C
- ✓ Subaru Lineartronic CVTF / high torque CVTF, K0425Y0710
- ✓ Honda HCF2
- ✓ Toyota TC / WS (CVT)
- ✓ Suzuki CVTF 3320 / TC / NS-2 / CVTF Green 1
- ✓ Dodge / Jeep / Chrysler (NS-2 / CVTF+4)
- ✓ Nissan NS-1 / NS-2
- ✓ BMW EZL 799A
- ✓ Mazda CVTF 3320
- ✓ Mitsubishi DiaQueen CVTF-J1
- ✓ Hyundai / Kia SP-CVT 1
- ✓ GM/Saturn DEX-CVT / GM CVT
- ✓ Mercedes Benz 236.20

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 24 June 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982