

PEAK SPEEDWAY 500

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK SPEEDWAY 500 is an SAE 50 high zinc, full synthetic formulation which provides ultimate protection for high performance engines on the racetrack or the highway. It's been proven in both field trials and on the track in petrol, methanol and nitromethane fuelled vehicles.

PEAK SPEEDWAY 500 has superior alcohol separation which assures continual lubricant protection to the engine. It increases engine efficiency and extends engine life. Its unique additive package suppresses the formation of deposits, sludge and varnish resulting in extended engine life

BENEFITS:

- Excellent sludge and deposit control.
- Extra zinc anti-wear additives protect the engine from excessive wear.
- Suitable for use with Methanol
- Reduces oil consumption

TYPICAL CHARACTERISTICS*:

| TEST | TYPICAL VALUE |
|---------------------------------|---------------|
| Density 15° C g/cm ³ | 0.865 |
| Viscosity 40°C cSt | 132 |
| Viscosity 100°C cSt | 17.2 |
| Viscosity Index | 142 |
| Flash Point °C | >215 |
| Zinc % | 0.220 |

PRODUCT SIZES:

| PRODUCT CODE | PACK SIZE | CTN QTY |
|--------------|-----------|---------|
| PKEFS500005 | 5 Litre | 4 |
| PKEFS500010 | 10 Litre | |
| PKEFS500020 | 20 Litre | |

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ SAE 50
- ✓ Recommended for four stroke racing engines using petrol, nitromethane or methanol

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 22 February 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982