



PEAK LS 140

PREMIUM MINERAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK LS 140 is a heavy-duty multigrade GL-5 gear lubricant containing extreme pressure additives. It is recommended for hypoid, LSD or spiral bevel differential, gear, transfer and reduction gearboxes of automotive equipment.

PEAK LS 140 is commonly used in differentials and manual transmissions in passenger cars, light commercial, 4WD, earthmoving and agricultural applications.

BENEFITS:

- Excellent non-chatter performance
- Excellent resistance to corrosion and foaming
- Excellent wear protection for prolonged gearbox life
- High load carrying ability
- Reduced transmission noise and smoother shifting

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.898
Viscosity 40°C cSt	362
Viscosity 100°C cSt	26.4
Viscosity Index	97
Flash Point °C	>210
Colour	L 3.5

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4 / GL-5
- ✓ API MT-1
- ✓ MACK GO-J
- ✓ SAE J2360

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGMLS140001	1 Litre	6
PKGMLS14002.5	2.5 Litre	4
PKGMLS140005	5 Litre	4
PKGMLS140020	20 Litre	
PKGMLS140060	60 Litre	
PKGMLS140205	205 Litre	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 24 June 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982