



PEAK READY-TO-USE COOLANT PREMIX

3 YEAR 100,000KM DRAIN INTERVAL

DESCRIPTION & APPLICATION:

PEAK Ready-To-Use Coolant Premix is coolant suitable for passenger cars, 4WD's and light duty diesel trucks. It contains approximately 350 grams per litre of ethylene glycol and will provide year-round protection from corrosion, overheating and freezing. It makes an excellent radiator top up fluid or full fill radiator coolant.

PEAK Ready-To-Use Coolant Premix gives your engine and cooling system extended multi-functional protection. It contains advanced corrosion inhibitors that will protect your engine and cooling system components, provides high heat transfer for more efficient cooling, anti-boil properties reducing coolant loss through overheating, plus antifreeze protection.

BENEFITS:

- Suitable for Aluminium, Brass, Cast Iron & Copper cooling systems
- Inhibits rust build up and mineral deposits, cavitation erosion, electrolysis and pitting
- Exceeds AS/NZS 2108.1 Coolant Type A 2004
- Compatible with all plastics, rubbers, and seals

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	1.05
Boiling Point °C	124
Freezing Point °C	-19
Flash Point °C (not mixed)	>120
Colour	Green

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKRC4SP005	5 Litre	4
PKRC4SP020	20 Litre	
PKRC4SP205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Exceeds AS/NZS 2108.1 Coolant Type A 2004

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 8 July 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



**Proudly Australian Owned
Since 1982**