



PEAK 5W20 C5 / SN

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W20 C5 SN is a premium synthetic engine oil formulated to meet the requirements of modern petrol and light duty diesel engines. It is recommended for passenger cars (including multi-valve, supercharged & turbocharged), 4WD's and light commercial vehicles including those with a diesel particulate filter (DPF) or other emission treatment devices.

PEAK 5W20 C5 SN is a low viscosity engine oil which meets the latest ACEA C5, API SN/CF and ILSAC GF-5 specifications. It is also suitable for hybrid engines in Toyota/Lexus, Nissan and Honda where an oil of this viscosity is recommended.

BENEFITS:

- Excellent sludge and deposit control.
- Outstanding low temperature performance for reduced wear on start-up.
- Improved engine resilience and fuel economy
- Reduces oil consumption

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.850
Viscosity 40°C cSt	43.3
Viscosity 100°C cSt	8.1
Viscosity Index	165
Flash Point °C	>215
Colour	L 3.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF520C5007	7 Litre	3
PKEF520C5020	20 Litre	
PKEF520C5205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ACEA C5
- ✓ API SN / CF
- ✓ ILSAC GF-5
- ✓ FORD WSS-M2C948-A, FORD WSS-M2C948-B
- ✓ STJLR.03.5004

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 7 April 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982