



PEAK TWO STROKE OIL

TWO STROKE OIL

DESCRIPTION & APPLICATION:

PEAK TWO STROKE OIL is formulated with low ash levels ensuring that it will readily mix with petrol.

PEAK TWO STROKE OIL Suitable to be mixed with petrol and used as a lubricant in air-cooled two stroke engines typically found in lawn mowers, brush cutters & chainsaws. May also be used in other small air-cooled two stroke engines at the manufacturers recommended fuel/oil dilution rates.

BENEFITS:

- keeps the engine clean by preventing ring sticking
- Prevents piston deposits
- Protects against plug fouling and exhaust deposits

NOTE: Not recommended for marine applications where NMMA TC-W3 is specified.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.871
Viscosity 40°C cSt	50.4
Viscosity 100°C cSt	7.8
Viscosity Index	123
Flash Point °C	>100
Colour	Blue

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKOTS.200	200 ML	
PKOTS001	1 Litre	
PKOTS005	5 Litre	
PKOTS020	20 Litre	
PKOTS205	205Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ JASO FC
- ✓ TISI
- ✓ API TC

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982