

PEAK AGRITRANS ULTRA

PREMIUM MINERAL UTTO

DESCRIPTION & APPLICATION:

PEAK AGRITRANS ULTRA is a multipurpose, 10W-30 UTTO (Universal Tractor & Transmission Oil) tractor transmission & hydraulic fluid manufactured using premium base oils and high-quality additive packages specifically designed to meet the requirement of **Case New Holland MAT 3540, Volvo VCE WB102 and Kubota Super UDT2.**

PEAK AGRITRANS ULTRA is formulated to offer an extreme performance over the standard UTTO due to its excellent shear stable properties and higher tolerance to water and corrosion.

BENEFITS:

- Exceptional frictional properties for brake chatter and brake capacity.
- Outstanding thermal and oxidation stability, non-foaming, zinc free, high shear stability formulation.
- Protects against sludge and varnish formation through superior dispersion.

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ SAE 10W30
- ✓ ISO 68 (Hydraulic Oil)
- ✓ SAE 80 (Gear Oil)
- ✓ API GL-4
- ✓ Caterpillar TO-2
- ✓ John Deere JDM J20C/D (HyGard)
- ✓ Allis-Chalmers Power fluid PF-821 XL
- ✓ Case New Holland MAT 3540
- ✓ Allision C-4
- ✓ Kubota UDT / Super UDT2/ Super UDT
- ✓ JCMAS HK P-041 / P-042
- ✓ Parker (Dension) HF-0 /1/2

- ✓ New Holland 410B
- AGCO Massey Ferguson CMS M1145 / M1143 / M1141 / M1135
- ✓ AGCO Massey Ferguson White Q-1826
- ✓ Volvo VCE WB 102
- ✓ ZFTE-ML-03E / 05F / 06E / 06F / 06K / 17E / 21F
- ✓ Eaton Vickers M-2950-S / 2952-S / 35VQ25 (pump stand)
- ✓ FNHA-2-C-201 / 200A / 200
- ✓ MS 1209 (Hytrans Ultra & Multi Tran) / 1207
 (Hytran Plus) / 1206

 PDS 1 19/09/2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing







PEAK AGRITRANS ULTRA

PREMIUM MINERAL UTTO

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE	
Density 15° Cg/cm³	0.8596	
Viscosity 40°C cSt	66.98	
Viscosity 100°C cSt	10.33	
Vis cosity Index	141	
Flash Point °C	>205	
Colour	L 1.0	

PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGMATE020	20 Litre	
PKGMATE205	205 Litre	
PKGMATE1000	1000 Litre	

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



