

PEAK ULTRA HONE OIL L

PREMIUM MINERAL HONNING OIL

DESCRIPTION & APPLICATION:

Peak Ultra Hone Oil L is a low viscosity mineral oil containing a high-performance chlorine/sulphur extreme pressure additive system.

Peak Ultra Hone Oil L is designed for general purpose automotive machine shop honing but can also withstand the most strenuous conditions required of a hone oil. It is excellent for con rods, piston pins, king pins, or general shop honing of cast iron, machining steel and aluminium. Also suitable for application including cylinder bore honing of hard and soft cast iron, chromium cast iron and steel liners. It is also suitable for flat honing operations on cast iron, lapping and superfinishing.

BENEFITS:

- Less oil "carry off" making cleaning easier due to its low viscosity
- Improvement in surface finishes with existing grade stones.
- Elimination of scoring.
- Employment of finer grade stones resulting in a higher standard of finish.
- Significant reduction in consumption (of up to 80%) compared to kerosene and kerosene blends.
- Reduction in unwanted vapours delivering cleaner conditions and improved shop hygiene

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
91310020	20 Litre	
91310205	205 Litre	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.870
Viscosity 40°C cSt	19.0
Viscosity Index	116
Flash Point °C	>90

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 7 April 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982