



PEAK LOMA UC 68

HYDRAULIC OIL – ULTRA CLEAR

DESCRIPTION & APPLICATION:

PEAK LOMA UC 68 is a high-performance, anti-wear hydraulic oil formulated using highly refined base oils with anti-wear, oxidation and corrosion inhibitors and anti-foam additives.

PEAK LOMA UC 68 is a thermally stable fluid capable of handling high loads and temperatures, and is compatible with most pumps, valves and seal materials used in hydraulic systems.

BENEFITS:

- Excellent wear and corrosion protection, ensuring good equipment life and decreased downtime
- Good thermal and oxidation stability characteristics permit higher operating temperatures and provide long fluid life.
- Excellent filterability to prevent filter blockages delivering increased filter life and reduced maintenance
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and improved equipment performance.

NOTE: PEAK LOMA UC 68 is not suitable for use with pumps containing silver plated components due to the zinc anti wear additives.

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.870
Kinetic Viscosity @ 40°C cSt	ASTM D7042	64.4
Kinetic Viscosity @ 100°C cSt	ASTM D7042	8.85
Viscosity Index	ASTM D2270	111
Flash Point °C	ASTM D92	>215

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIHM68UC020	20 Litre	
PKIHM68UC205	205 Litre	
PKIHM68UC1000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Cincinnati Milacron P68 / P69 / P70
- ✓ Denison HF-0 / HF-1 / HF-2
- ✓ DIN 51 524 Part 2 (HLP)
- ✓ Vickers 1-286-S / M2952-S
- ✓ US Steel 136 / 127

LOMA UC 68 meets the requirements of the following pump manufacturers:

Hagglund, Rexroth, Danfoss, Linde, Commercial Hydraulics, Bosch, Racine, Vickers, Sunstrand, Denison, Oilgear, Cincinnati Milacron

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 19 September 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982