



PEAK 5W30 C1

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 C1 engine oil is a highly advanced engine oil that is formulated to meet low SAPS requirements making it compliant with the demanding requirements of Euro 4 and Euro 5 exhaust emission legislation.

PEAK 5W30 C1 has been specially developed for petrol and diesel engines with particulate filters and meets the requirements for Ford, Jaguar, Mazda and Mitsubishi and all other engines requiring ACEA C1, JASO DL-1, Ford M2C-934B and Jaguar, Land Rover ST JLR.03.5005

BENEFITS:

- Reliable protection under extreme conditions and high temperatures.
- Excellent wear protection
- Extended service life
- Improved power and fuel economy

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.852
Viscosity 40°C cSt	54.6
Viscosity 100°C cSt	9.8
Viscosity Index	167
Flash Point °C	>200
Colour	1.5
Sulphated Ash %	0.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEFC1530005	5 Litre	4
PKEFC1530010	10 Litre	
PKEFC1530020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ACEA C1
- ✓ JASO DL-1
- ✓ Ford WSS M2C-934B
- ✓ Jaguar Land Rover ST JLR.03.5005

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 20 October 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982