



PEAK 25W50

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 25W50 is a general-purpose multi grade engine oil for unleaded, lead replacement and LPG passenger vehicle engines. It is suitable for regularly serviced vehicles and the value conscious motorist.

PEAK 25W50 is best suited for vehicles manufactured before 1994.

BENEFITS:

- Provides suitable protection for vehicles pre 1994.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.885
Viscosity 40°C cSt	158.1
Viscosity 100°C cSt	16.98
Viscosity Index	115.4
Flash Point °C	>220
Colour	L 3.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEM2050004	4 Litre	4

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SH/CD
- ✓ SAE 25W50

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 June 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982