



## PRODUCT DATA SHEET

# PEAK 15W40

## ADVANCED MINERAL ENGINE OIL

### PRODUCT DESCRIPTION

PEAK 15W40 is a high quality engine oil formulated with premium mineral base oils and high-performance additives making it suitable for engines requiring API SN and ACEA A3/B4.

PEAK 15W40 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter. This product is suitable for diesel vehicles.

### BENEFITS

- Outstanding thermal and oxidation stability
- Excellent detergent additives to improve engine cleanliness
- Engine seals stay soft and pliable to minimise and reduce oil leakages

### SPECIFICATIONS AND PERFORMANCE LEVEL

- API SN
- ACEA A3/B4
- VW 501.01 / 505.00
- ACEA A3/B3

### CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm <sup>3</sup>	0.8
Viscosity @ 40°C cSt	110.8
Viscosity @ 100°C cSt	14.9
Viscosity Index	139.6
Flash Point °C	>195
Colour	L3.0

### PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEM1540001	1 Litre	6	780
PKEM1540005	5 Litre	4	192
PKEM1540020	20 Litre		48
PKEM1540205	205 Litre		4
PKEM15401000	1000 Litre		

PDS published on 07 Mar 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 | WEB: [www.peakoil.com.au](http://www.peakoil.com.au)

