

PEAK SYNPRO DIESEL 5W40

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK SYNPRO DIESEL 5W40 is a premium semi synthetic engine oil formulated to meet the requirements of modern vehicles fitted with a Diesel Particulate Filter (DPF) requiring a low ash oil. It is particularly recommended for common rail and direct injection diesel engines. It is also recommended for both agricultural and earthmoving equipment where API CJ-4 or CI-4 is required by the OEM.

PEAK SYNPRO DIESEL 5W40 is also a good all round engine lubricant suitable in petrol multi-cam, multi-valve, turbocharged, supercharged and naturally aspirated engines.

BENEFITS:

- Suited to vehicles requiring a CJ-4 Low ash oil.
- Specially formulated for engines fitted with a DPF
- Excellent sludge and deposit control.
- Outstanding low temperature performance for reduced wear on start-up.
- Improved engine resilience and fuel economy
- Reduction in oil consumption.

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDS540007	7 Litre	3
PKDS540020	20 Litre	
PKDS540205	205 Litre	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.856
Viscosity 40°C cSt	89.4
Viscosity 100°C cSt	14.4
Viscosity Index	167
Flash Point °C	>215
Colour	L 4.0

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API CJ-4
- ✓ ACEA E9, Cummins CES 20081
- ✓ Mack EO-O Premium Plus
- ✓ Cat ECF-3
- ✓ Volvo VDS 4
- ✓ Renault RLD 3
- ✓ Detroit Diesel DDC93K218

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 12 August 2022