



PEAK WD FLUID

Water Displacing Fluid

DESCRIPTION & APPLICATION:

PEAK WD FLUID is formulated to penetrate and protect motors, chains, cables, sprockets and hubs. It also frees up rusty nuts and bolts, inhibits rust and corrosion, displaces dirt and water. Also useful in marine applications; on shackles, locks, hatches, bearings, winches and hinges.

BENEFITS:

- Lubricates & Protects metal surfaces
- Penetrates corroded parts to allow easier extraction
- Displaces moisture

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Appearance	Clear Tan Liquid
Density 15°C g/cm ³	0.850
Flash Point °C	42

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKSWD020	20 Litre	
PKSWD205	205 Litre	
PKSWD1000	1000 Litre	

DIRECTIONS FOR USE:

Apply by spraying directly on to surface, brushing on or dipping parts into fluid.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 29 July 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982