

PEAK LONG LIFE GREEN COOLANT

PREMIX 50%

5 YEAR 250,000KM DRAIN INTERVAL

DESCRIPTION & APPLICATION:

PEAK Long Life Green Coolant Premix 50% is an Ethylene Glycol OAT based coolant formulated with a proprietary corrosion inhibitor package. This is Silicate, Borate, Phosphate, Amine and Nitrate free providing ideal protection for of all engine metals including aluminium and ferrous alloys for up to 5 years.

PEAK Long Life Green Coolant Premix 50% provides anti-freeze and anti-boil additives that provide the best balance of protection against freezing, corrosion and overheating. Suitable for use in diesel trucks, buses, agricultural and earthmoving applications as well as passenger cars and stationary engines. It can be used straight when coolant concentrations of 50% are required.

BENEFITS:

- Silicate, Borate, Phosphate, Amine and Nitrite free
- Excellent choice for use in mixed fleets
- Long drain intervals
- Compatible with all plastics, rubbers, seals and aluminium

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKRLG50020	20 Litre	
PKRLG50205	205 Litre	
PKRLG501000	1000 Litre	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	1.05
Boiling Point °C	127
Freezing Point °C	-37
Flash Point °C (not mixed)	>120
Colour	Green

SPECIFICATIONS & PERFORMANCE LEVEL:

- | | | |
|---------------|------------------------------------|--------------------|
| ✓ ASTM D-3306 | ✓ AS/NZS 2108.1Coolant Type A 2004 | ✓ GM1825M/ 1899M |
| ✓ ASTM D-6210 | ✓ John Deere JDM H24B1 / C1 | ✓ Cummins 90T8-4 |
| ✓ ASTM D-4985 | ✓ Ford WSS-M97B44-C | ✓ J.I. Case JIC501 |
| ✓ SAE J1034 | | |

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 24 June 2022

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982