

PEAK ISO 220 SYNTHETIC INDUSTRIAL GEAR OIL

FULL SYNTHETIC NON-EP

DESCRIPTION & APPLICATION:

PEAK ISO 220 SYNTHETIC INDUSTRIAL GEAR OIL (Non-EP) is formulated with an optimum level of anti-wear additive to provide maximum protection against scuffing and wear in system applications. Non-EP additives are used to ensure soft metals found in many pumps and gear housings have an extended service life with no adverse effects

BENEFITS:

- Provides excellent wear protection for soft metals while under extreme pressures
- Protects against rust and corrosion.
- Resistance to Foaming and Oxidisation.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° Cg/cm ³	0.895
Viscosity 40°C cSt	224.9
Viscosity 100°C cSt	30.3
Viscosity Index	176.1
Flash Point °C	>210
Colour	L0.5

SPECIFICATIONS & PERFORMANCE

LEVEL:

- ✓ DIN 51524
- ✓ US STEEL 127 / 136

PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIGF220NEP020	20 Litre	
PKIGF220NEP205	205 Litre	

PDS 1 19/10/2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.