



PRODUCT DATA SHEET

PEAK 0W20

FULL SYNTHETIC ENGINE OIL

PRODUCT DESCRIPTION

PEAK 0W20 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SQ and ILSAC GF-7.

PEAK 0W20 with API SQ and ILSAC GF-7 performance claims include new performance requirement such as aged oil LSPI protection and enhanced performance with tighter fuel economy limits, tighter deposit control limits, and extended durability through stringent wear control limits.

PEAK 0W20 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol, low emission engines, and hybrids vehicles. It is recommended for passenger cars, 4WD's, and light commercial vehicles where Petrol, E10, and E85 fuels are used.

BENEFITS

- Improved power and engine responsiveness
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGD engines
- Excellent deposit control

SPECIFICATIONS AND PERFORMANCE LEVEL

- API SQ
- ILSAC GF-7

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm ³	0.85
Viscosity @ 40°C cSt	44.1
Viscosity @ 100°C cSt	8.3
Viscosity Index	167.5
Flash Point °C	>210
Colour	L2.0

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEF020005	5 Litre	4	192
PKEF020010	10 Litre		75
PKEF020020	20 Litre		32
PKEF020205	205 Litre		4

PDS published on 17 Apr 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 | WEB: www.peakoil.com.au

