

PEAK FOOD MACHINERY GREASE

ALUMINIUM COMPLEX GREASE - NLGI 2

DESCRIPTION & APPLICATION:

Peak Food Machinery Grease is a premium, multipurpose high temperature, extreme pressure aluminium complex NLGI No. 2 grease specifically designed for use in the Food Industry, it is white, odourless and tasteless

Peak Food Machinery Grease is recommended for use in most grease applications encountered in food processing plants. It is suitable for rolling element bearings, plain bearings, gears and couplings.

Peak Food Machinery Grease is also approved by the Department of Primary Industries and Energy as Food Grade Lubricant TYPE A, AQIS Approved: Number IOA 101, Halal Certified and ruled acceptable by the U.S. Department of Agriculture for the processing machinery in federally inspected meat and poultry processing plants.

BENEFITS:

- Registered with NSF (category H-1) and meets the requirements of Section 178.3570 of the Food and Drug Administration (FDA) regulations.
- High degree of thermal, mechanical stability and provides superior protection against rust and corrosion
- High load carrying capacity which protects equipment against extreme loading
- Good water resistance against water spray & washout.

TYPICAL CHARACTERISTICS*:

TEST TYPICAL VALUE		
NLGI Grade	2	
Soap/Thickener Type	Aluminium Complex	
Dropping point °C	265	
Oil Viscosity 40°C cSt	220	
4 Ball Weld Load, Kg	200	
Operating Temperature Range °C	-30°C to 160°C	
Colour	White	

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXFM.450	450 G	12
PKGXFM020	20 KG	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 7 April 2021







ABN: 74 8875 10101