



PEAK FM GREASE

ALUMINIUM COMPLEX GREASE - NLGI 2

PRODUCT DESCRIPTION

PEAK FM GREASE is a premium, multipurpose high temperature, extreme pressure aluminium complex NLGI No. 2 grease specifically designed for use in the Food Industry. It is white, odourless and tasteless.

PEAK FM GREASE is recommended for use in most grease applications encountered in food processing plants. It is suitable for rolling element bearings, plain bearings, gears and couplings.

PEAK FM GREASE is also approved by the Department of Primary Industries and Energy as Food Grade Lubricant TYPE A, Halal Certified and ruled acceptable by the U.S. Department of Agriculture for the processing machinery in federally inspected meat and poultry processing plants.

BENEFITS

- Registered with NSF (category H-1) and meets the requirements of Section 178.3570 of the Food and Drug Administration (FDA) regulations
- High degree of thermal, mechanical stability and provides superior protection against rust and corrosion
- High load carrying capacity which protects equipment against extreme loading
- Good water resistance against water spray and washout

CHARACTERISTICS

Test	Typical Value
NLGI Grade	2
Soap/Thickener Type	Aluminium Complex
Dropping Point °C	265
Oil Viscosity @ 40°C cSt	220
4 Ball Weld Load kg	400
Operating Temperature Range °C	-30 to 160
Colour	White

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKGXFM.450	450 g	20	
PKGXFM020	20 kg		32

PDS published on 17 Mar 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.

