

# PEAK A/C OIL ISO 46

## AIR COMPRESSOR OIL

### DESCRIPTION & APPLICATION:

PEAK A/C ISO 46 is a premium quality compressor oil specifically formulated to provide outstanding lubrication, performance and protection for rotary sliding vane and screw air compressors. It uses an advanced additive system to deliver exceptional performance for compressors operating at up to 100°C discharge temperatures and with 6,000-hour oil drain periods.

PEAK A/C ISO 46 Excellent chemical and thermal stability ensuring good service life of the lubricant and compressor components resulting in reduced equipment downtime and maintenance costs.

### BENEFITS:

- Promotes operational efficiency via reducing foaming
- Exceptional cleanliness and filtering ability even when subjected to moisture or water contamination

**Note:** This product is not recommended for breathing air unit compressors.

### TYPICAL CHARACTERISTICS\*:

| TEST                            | TYPICAL VALUE |
|---------------------------------|---------------|
| Density 15° C g/cm <sup>3</sup> | 0.863         |
| Viscosity 40°C cSt              | 42.6          |
| Viscosity 100°C cSt             | 6.7           |
| Viscosity Index                 | 110           |
| Flash Point °C                  | >210          |
| Colour                          | L 0.5         |

### PRODUCT SIZES:

| PRODUCT CODE | PACK SIZE | CTN QTY |
|--------------|-----------|---------|
| PKIAM046001  | 1 Litre   | 6       |
| PKIAM046005  | 5 Litre   | 4       |
| PKIAM046020  | 20 Litre  |         |
| PKIAM046205  | 205 Litre |         |

### SPECIFICATIONS & PERFORMANCE LEVEL:

✓ DIN 51 506 VBL / VCL / VDL

✓ ISO DP6521 DAH

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 2 February 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982