



PEAK 20W50

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 20W50 is a high-quality engine oil formulated with a combination of premium mineral base oils and high-performance additives making it suitable for engines requiring API SM.

PEAK 20W50 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter.

BENEFITS:

- Outstanding thermal and oxidation stability
- Outstanding shear stability
- Excellent detergent additives to improved engine cleanliness.
- Engine seals stay soft and pliable to minimize and reduce oil leakages.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.879
Viscosity 40°C cSt	148
Viscosity 100°C cSt	17
Viscosity Index	124
Flash Point °C	>220
Colour	L 2.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
TP205020L	20 Litre	
TP2050205L	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SM

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 25 March 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982