

PEAK 75W85

SEMI SYNTHETIC GEAR OIL - API GL-4

DESCRIPTION & APPLICATION:

PEAK 75W85 uses a blend of synthetic and high-quality mineral base fluids. The 75W85 viscosity assists with cold gear changes and provides gear protection at high operating temperatures.

PEAK 75W85 is suitable for manual gearboxes, transfer cases and transaxles in passenger cars, 4WDs and trucks that specify the use of a 75W85 oil meeting API GL-4, it is also suitable for electric and manual shift outboard gear boxes, hydraulic tilt mechanisms and stern drive gearboxes.

BENEFITS:

- High viscosity index
- Excellent low-temperature properties
- shear stable formulation
- Will not harm brass or bronze
- excellent wear protection

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.853
Viscosity 40°C cSt	78.5
Viscosity 100°C cSt	12.8
Viscosity Index	164
Flash Point °C	>205
Colour	L 1.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGS758502.5	2.5 Litre	4
PKGS7585020	20 Litre	
PKGS7585060	60 Litre	
PKGS7585205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4
- ✓ ZF TE-ML 24A
- ✓ ZF TE-ML 08

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 16 November 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982