



PRODUCT DATA SHEET

PEAK 0W16

FULL SYNTHETIC ENGINE OIL

PRODUCT DESCRIPTION

PEAK 0W16 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SQ and ILSAC GF-7B.

PEAK 0W16 with API SQ and ILSAC GF-7B performance claims include new performance requirement such as aged oil LSPI protection and enhanced performance with tighter fuel economy limits, tighter deposit control limits, and extended durability through stringent wear control limits.

PEAK 0W16 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol, low emission engines, and hybrid vehicles. It is recommended for passenger cars, 4WD's, and light commercial vehicles where Petrol, E10, and E85 fuels are used.

BENEFITS

- Specially designed for hybrid vehicles
- Improved power and engine responsiveness
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGD engines
- Excellent deposit control

SPECIFICATIONS AND PERFORMANCE LEVEL

- API SQ
- ILSAC GF-7B

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm ³	0.847
Viscosity @ 40°C cSt	38.1
Viscosity @ 100°C cSt	7.4
Viscosity Index	165
Flash Point °C	>210
Colour	L2.0

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEF016007	7 Litre	3	108
PKEF016020	20 Litre		32
PKEF016205	205 Litre		4

PDS published on 20 Aug 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

<https://go.lupinsys.com/peaklubricants/harms/pm/3ce53477fb2860b837513143011b3db2-published/attachment/sds.pdf>

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 | WEB: www.peakoil.com.au

