

# PEAK AC 100 COMPRESSOR OIL

## AIR COMPRESSOR OIL

### DESCRIPTION & APPLICATION:

PEAK AC 100 is a premium compressor oil formulated to provide outstanding lubrication, performance and protection of high pressure reciprocating (piston) compressors operating at air discharge temperatures of up to 220°C and rotary screw air compressors (oil flooded or oil injected) single or two-stage compressors operating at pressures of up to 20 bar and with air discharge temperatures of up to 100°C.

### BENEFITS:

- Excellent chemical and thermal stability ensuring good service life
- Outstanding wear protection
- Reduced foaming and exceptional cleanliness and filtering ability
- Anti-clogging property which extends the life of the separating filter elements

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.871
Kinetic Viscosity @ 40°C cSt	102.5
Kinetic Viscosity @ 100°C cSt	11.8
Viscosity Index	104
Flash Point °C	>210
ASTM Colour	L 0.5

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIAM0100001	1 Litre	6
PKIAM0100005	5 Litre	4
PKIAM0100020	20 Litre	
PKIAM0100205	205 Litre	
PKIAM01001000	1000 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 6743-3A:2003 L-DAA
- ✓ DIN 51506 VBL

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 15 August 2021

### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982