



# PEAK RED RUBBER GREASE

## BENTONITE GREASE - NLGI 2.0

### DESCRIPTION & APPLICATION:

PEAK RED RUBBER Grease is premium quality clay thickened grease formulated with Castor Oil. The grease is specifically formulated for a wide range of automotive and industrial applications where contact with natural and/or synthetic rubber components is required or likely. These include hydraulic dust covers, braking system components, seals, washers, stoppers, tyre rims etc.

PEAK RED RUBBER Grease will not adversely affect rubber parts therefore preventing excessive softening or hardening.

### BENEFITS:

- Compatible with natural & synthetic rubbers
- Excellent lubricity
- Easy to apply
- Protects against rust and corrosion
- Environmentally Friendly Ingredients

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
NLGI Grade	2
Soap/Thickener Type	Inorganic Clay
Dropping point °C	>280
Operating Temperature °C	-10 to 80
Oil Viscosity @ 40°C	250
Colour	Red

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGRRRG.500	500G	12

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 18 April 2022



**PEAK LUBRICANTS PTY LTD**  
**HEAD OFFICE:** 224-230 South Gippsland Highway, Dandenong South VIC 3175  
**PHONE:** 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256  
**EMAIL:** tech@peakoil.com.au / **WEB:** www.peakoil.com.au  
**ABN:** 74 8875 10101



**Proudly Australian Owned**  
Since 1982