

PEAK SYNPRO DIESEL 15W40

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK SYN PRO DIESEL 15W40 is a low SAPS (sulphur and phosphorous) product that incorporates the most advanced development in lubrication chemistry and high viscosity index semi synthetic base oils resulting in a high- performance diesel engine oil.

PEAK SYN PRO DIESEL 15W40 has been formulated specifically to meet the requirements of Australian and imported designed low emission engines including those engines which incorporate exhaust gas recycling (EGR) to provide fuel efficiency, high wear protection and long drain capability. EGR can add to deposits forming in the combustion chamber, and therefore the low sulphated ash content assists in maintaining engine cleanliness.

PEAK SYN PRO DIESEL 15W40 is recommended for high speed, turbo charged four stroke LPG and petrol engines, in particular all emission design engines. Designed to protect emission control systems, help comply with emission standards, reduce engine wear and control piston deposits and oil consumption.

PEAK SYN PRO DIESEL 15W40 is specially formulated to protect exhaust after treatment devices such as diesel particulate filters (DPFs). Fortified to reduce valve stem and guide wear normally associated with the dryness or lack of lubricity that is characteristic of an LPG fuel. Importantly, as LPG engines generally run hotter than a petrol engine. Possesses the oxidation resistance necessary to prolong lubricant life preventing oil thickening and combat the effect of acidic attack from nitrous oxides that damage soft metal bearing materials.

BENEFITS:

- Designed to protect emission control systems
- Provides fuel efficiency, high wear protection and long drain capability
- Reduces engine wear and control piston deposits and oil consumption
- Formulated to protect exhaust after treatment devices such as diesel particulate filters (DPFs)

SPECIFICATIONS & PERFORMANCE

LEVEL:

- | | |
|------------------------------------|-------------------------------------|
| ✓ S.A.E Grade 15W40 | ✓ Cummins CES 20081 / 20077 / 20076 |
| ✓ API CJ-4/SM | ✓ DDC 93K218 |
| ✓ Caterpillar ECF-3, ECF-2, ECF-1a | ✓ M.T.U Type 2.1 |
| ✓ ACEA E9/E7 | ✓ VOLVO VDS4, VDS3 |
| ✓ MB 228.31 | ✓ MAN 3575 |
| ✓ Mack EO-O Premium Plus | ✓ Renault RLD-3 |

PDS 118/06/2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982



PEAK SYNPRO DIESEL 15W40

SEMI SYNTHETIC ENGINE OIL

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C Kg/l	0.878
Viscosity 40°C cSt	113
Viscosity 100°C cSt	14.9
Viscosity Index	165
Flash Point °C	>226
TBN	9.9

PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDS1540020	20 Litre	
PKDS1540205	205 Litre	

PDS 118/06/2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982