



# PEAK SYN TORA 320

## FULL SYNTHETIC INDUSTRIAL GEAR OIL

### DESCRIPTION & APPLICATION:

PEAK SYN TORA 320 is an advanced synthetic industrial gear oil which delivers outstanding performance under severe operating conditions such as high loads and wide temperature variations. It has been specially developed to reduce friction and deliver long service life.

PEAK SYN TORA 320 is designed to resist micro-pitting and maintain system efficiency.

### BENEFITS:

- Long service life reduces maintenance costs
- Excellent wear and corrosion protection
- High film strength for superior wear protection and load carrying capability even under shock loading conditions
- Outstanding flow properties over a wide temperature range enhances the efficiency of industrial gear systems

### TYPICAL CHARACTERISTICS\*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	ASTM D7042	0.906
Viscosity @ 40°C cSt	ASTM D7042	325
Viscosity @ 100°C cSt	ASTM D7042	40.5
Viscosity Index	ASTM D2270	178
Flash Point °C	ASTM D92	>230

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIGF0320020	20 Litre	
PKIGF0320205	205 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ US Steel 224
- ✓ AGMA 9005-F16
- ✓ DIN 51517-3 (CLP)
- ✓ David Brown S1.53.106

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 29 March 2022



**PEAK LUBRICANTS PTY LTD**  
**HEAD OFFICE:** 224-230 South Gippsland Highway, Dandenong South VIC 3175  
**PHONE:** 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256  
**EMAIL:** tech@peakoil.com.au / **WEB:** www.peakoil.com.au  
**ABN:** 74 8875 10101



**Proudly Australian Owned**  
**Since 1982**