



## PRODUCT DATA SHEET

# PEAK 5W40 SP

## FULL SYNTHETIC ENGINE OIL

### PRODUCT DESCRIPTION

PEAK 5W40 SP is a premium synthetic engine oil formulated to meet both the latest API SP specification and the European ACEA A3/B4 requirements.

PEAK 5W40 SP is recommended for use in modern multi-cam, multi-valve, turbocharged, supercharged and naturally aspirated petrol engines.

### BENEFITS

- Excellent sludge and deposit control
- Outstanding low temperature performance for reduced wear on start-up
- Improved engine resilience and fuel economy
- Reduction in oil consumption
- Improved Low Speed Pre-Ignition (LSPI) protection

### SPECIFICATIONS AND PERFORMANCE LEVEL

- API SP
- ACEA A3/B4
- BMW Longlife-01
- MB 229.5
- VW 502.00 / 505.00
- PSA B71 2296
- Porsche A40
- Renault RN0700 / RN0710

### CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm <sup>3</sup>	0.853
Viscosity @ 40°C cSt	80.6
Viscosity @ 100°C cSt	13.6
Viscosity Index	170
Flash Point °C	>215
Colour	L3.5

### PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEF540001	1 Litre	6	780
PKEF540007	7 Litre	3	108
PKEF540020	20 Litre		32
PKEF540205	205 Litre		4

PDS published on 23 Apr 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



**Peak Lubricants Pty Ltd**  
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175  
PHONE: 03 9799 0977 | WEB: [www.peakoil.com.au](http://www.peakoil.com.au)

