



PEAK DRAWING OIL WW

DRAWING AND EXTRUSION FLUID

DESCRIPTION & APPLICATION:

PEAK DRAWING OIL WW is a viscous extreme pressure concentrate formulated using a paraffinic base oil. It is specially designed for deep drawing and extrusion operations, particularly stainless steel and brass.

PEAK DRAWING OIL WW can also be used for brushing on metal parts during machining operations.

FEATURES & BENEFITS:

- Can be used neat or diluted with water depending on the severity of the operation
- Water washable for easy "clean up".
- Excellent Die protection
- Improvement in surface finish

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.99
Kinetic Viscosity @ 40°C cSt	233.7
Kinetic Viscosity @ 100°C cSt	17.7

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKICMDWW020	20 Litre	
PKICMDWW205	205 Litre	

APPLICATION :

- Use undiluted for metal drawing, stamping, etc. and hand application for machining operations.
- The product is viscous and is satisfactory for pumping and spraying.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 4 August 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982