

PEAK WHITE OIL 32

PREMIUM MINERAL WHITE OIL

DESCRIPTION & APPLICATION:

PEAK WHITE OIL 32 is a white mineral oil specially processed and packaged to ensure full compliance with the purity standards of the U.S. Pharmacopoeia (USP) and British Pharmacopoeia (BP).

PEAK WHITE OIL 32 complies with U.S. Food and Drug Administration (FDA) Regulation CFR 172.878 for light mineral oil that is permitted to be included, within restrictions, in foods and CFR 178.3620 (a) for mineral oil for use in non-food articles that will come in contact with food. Suitable in a wide variety of food processing and packaging operations where a lubricating oil used as a processing aid may be included in a food or food packaging material.

PEAK WHITE OIL 32 can be used in the manufacture of pharmaceutical and cosmetic preparations such as ointments, creams and massage oils, Used as a plasticiser for hydrocarbon resins, as a process oil where extremely low sulphur contents are required and as lubricants for sewing, knitting, and cloth cutting machines where a stainless mineral oil is desired, other industrial uses include agricultural sprays, organic synthesis, plastics manufacture and animal husbandry.

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIWO32205	205 Litre	

BENEFITS:

- High degree of purity, water-white product that contains no toxic impurities.
- Exceeding oxidation and light stability of standard process oils

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15°C g/cm³	0.850
Viscosity 40°C cSt	32
Flash Point °C	>210
Pour Point °C	-12 Max
Colour (Saybolt)	+30
Polycyclic Aromatics	Passes
Carbonisable Substances	Passes
Odour	Odourless

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 7 April 2021 * Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



