

# PEAK CHAIN BAR OIL 125

## CHAIN SAW BAR OIL ISO 125

### DESCRIPTION & APPLICATION:

Peak Chain Bar Oil is specifically developed for the lubrication of chain and guide bars of modern chain saws, it provides good protection against wear, rust and corrosion and has good low temperature properties, contains a tackiness agent that protects chains, bars and sprockets on chainsaws.

Peak Chain Bar Oil is suitable for use with both automatic and manually operated oil systems and can be used on other chain driven equipment including motorcycles, lawnmowers, lumber carriers and farm equipment.

### BENEFITS:

- Forms a strong tacky lubricating film that provides good wear protection
- Excellent protection against rust and corrosion
- Good adherence to metal surfaces ensuring optimum bar and chain life

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.880
Viscosity 40°C cSt	125
Viscosity 100°C cSt	17.5
Viscosity Index	154
Flash Point °C	>230
Pour Point	-15

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKOCO125020	20 Litre	
PKOCO125205	205 Litre	
PKOCO1251000	1000 Litre	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982