



PEAK STAMPING OIL R5211

BIODEGRADABLE COMPOUNDED STAMPING OIL

DESCRIPTION & APPLICATION:

PEAK STAMPING OIL R5211 is a specially compounded vegetable based bio-degradable lubricant designed for light punching, stamping and sawing of aluminium products.

PEAK STAMPING OIL R5211 can be used undiluted in dripper systems for stamping operations. It can also be applied by roller coating, dipping and hand brushing applications for machining operations. May also be used in spray applications where airless spraying is required.

BENEFITS:

- Biodegradable & Non Toxic
- Can be applied by spray, roller coating, dipping and hand brushing
- Specially formulated for use on Aluminium

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.900
Kinemattic Viscosity @ 100°C cSt	ASTM D7042	3.8
Kinemattic Viscosity @ 40°C cSt	ASTM D2270	12.6
Flash Point °C	ASTM D92	> 150

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
91520020	20 Litre	n/a
91520205	205 Litre	n/a

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 8 November 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982