



PRODUCT DATA SHEET

PEAK 5W30 FE

FULL SYNTHETIC ENGINE OIL

PRODUCT DESCRIPTION

PEAK 5W30 FE is a full synthetic engine oil that is specifically designed for fuel economy with premium quality additives for engine protection and sludge control.

PEAK 5W30 FE is suitable for petrol, light duty diesel engines and diesel vehicles fitted with a Diesel Particulate Filter (DPF) where the specifications ACEA A5/B5, Ford WSS-M2C913-D are required.

BENEFITS

- Outstanding thermal and oxidation stability for longer oil life
- Enhanced frictional properties for less wear and fuel consumption
- Maintains viscosity and performance even at extreme temperatures
- Excellent flow characteristics even at very low temperatures

SPECIFICATIONS AND PERFORMANCE LEVEL

- API SL
- ACEA A5/B5
- Renault RN0700
- Ford WSS-M2C913-D / WSS-M2C913-C / WSS-M2C913-B
- Jaguar Land Rover STJLR.03.5003

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm ³	0.851
Viscosity @ 40°C cSt	53.8
Viscosity @ 100°C cSt	9.9
Viscosity Index	172
Flash Point °C	>210
Colour	L2.0
Sulphated Ash	1.1

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEF530F001	1 Litre	6	780
PKEF530F005	5 Litre	4	192
PKEF530F007	7 Litre	3	108
PKEF530F010	10 Litre		75
PKEF530F020	20 Litre		32
PKEF530F205	205 Litre		4
PKEF530F1000	1000 Litre		

PDS published on 23 Apr 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 | WEB: www.peakoil.com.au

