



PRODUCT DATA SHEET

PEAK 5W30 DX-1

FULL SYNTHETIC ENGINE OIL

PRODUCT DESCRIPTION

PEAK 5W30 DX-1 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SQ, dexos1™ Gen 3 and ILSAC GF-7. PEAK 5W30 DX-1 is engineered for excellence, with the Gen 3 formulation delivers superior wear protection, enhanced fuel efficiency, and lower emissions.

PEAK 5W30 DX-1 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol engines, and hybrids vehicles. It is recommended for passenger cars, 4WD's, and light commercial vehicles where Petrol, E10 and E85 fuels are used.

BENEFITS

- Improved power and engine responsiveness
- Excellent deposit control
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGD engines

SPECIFICATIONS AND PERFORMANCE LEVEL

- API SQ
- dexos1™ Gen 3
- ILSAC GF-7

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm³	0.85
Viscosity @ 40°C cSt	54.97
Viscosity @ 100°C cSt	10.15
Viscosity Index	174
Flash Point °C	>215
Colour	L2.5

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKEFD1530005	5 Litre	4	192
PKEFD1530010	10 Litre		75
PKEFD1530020	20 Litre		32
PKEFD1530205	205 Litre		4

PDS published on 17 Apr 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 | WEB: www.peakoil.com.au

