



PEAK 25W70

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 25W70 is an exceptionally high viscosity multi-grade engine lubricant. It is formulated for use in worn or older style passenger vehicles and other large four stroke engines or where a high viscosity is preferred due to harsh operating conditions.

BENEFITS:

- Assists to increase oil pressure.
- Control and minimise oil consumption.
- High Zinc for extra protection for flat tappet cam systems.
- Suitable for use in extreme operating conditions such as heavy towing, rallying and racing.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.898
Viscosity 40°C cSt	310.0
Viscosity 100°C cSt	27.73
Viscosity Index	119.8
Flash Point °C	>220
Colour	L 4.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEM2570005	5 Litre	4
PKEM2570020	20 Litre	
PKEM2570205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SL/CF
- ✓ SAE 25W70

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 June 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982