



PEAK 75W80 GL-4

MINERAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK 75W80 GL-4 gear oil is a premium mineral gear oil formulated to provide maximum protection to manual transmissions without compromising soft metal components such as synchro rings.

PEAK 75W80 GL-4 gear oil is suitable to be used in transmissions with spiral bevel gears or hypoid gears operating under moderate speeds and loads. PEAK 75W80 GL-4 has excellent resistance to corrosion and foaming. The low 75W80 viscosity will aid the transmission to change effortlessly between gearchanges.

BENEFITS:

- Excellent Anti-wear protection.
- Low viscosity to allow for easier and smoother gear shifting.
- Compatible with soft metals.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.858
Viscosity 40°C cSt	52.8
Viscosity 100°C cSt	8.8
Viscosity Index	145
Flash Point °C	>215
Colour	L 0.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGM7580001	1 Litre	6
PKGM7580005	5 Litre	4
PKGM7580020	20 Litre	
PKGM7580060	60 Litre	
PKGM7580205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4
- ✓ SAE 75W80
- ✓ ZF TE-ML 08
- ✓ ZF TE-ML 24A

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 19 May 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982