

PEAK C3 5W30

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK C3 5W30 is a mid-SAPS / Low Ash synthetic engine oil formulated to meet the demands and fuel efficiency expectations of the latest petrol and diesel engines, suitable for use where API SN, ACEA C3, MB 229.52 and GM Dexos2™ are required.

PEAK C3 5W30 is recommended for use in modern turbocharged, supercharged and naturally aspirated petrol engines, diesel engines fitted with Diesel Particulate Filters (DPF) and hybrid vehicles.

BENEFITS:

- Excellent soot and sludge control
- Extended engine oil drain intervals.
- Mid SAPS (Sulphated Ash, Phosphorus and Sulphur).
- Outstanding low temperature performance for reduced wear on start-up.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.854
Viscosity 40°C cSt	69.0
Viscosity 100°C cSt	11.4
Viscosity Index	161.0
Flash Point °C	>215
Sulphated Ash	0.8
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEFC3530001	1 Litre	6
PKEFC3530005	5 Litre	4
PKEFC3530005	7 Litre	3
PKEFC3530010	10 Litre	
PKEFC3530020	20 Litre	
PKEFC3530205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN / CF
- ✓ ACEA C3
- ✓ MB-Approval 229.52
- ✓ MB-Approval 229.31/229.51
- ✓ BMW LL-04 (Long Life -04)
- ✓ GM Dexos2™
- ✓ Renault RN0700 / RN0710

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982