

PEAK LOMA XLT 15 HYDRAULIC OIL - EXTRA LOW TEMP

DESCRIPTION & APPLICATION:

PEAK LOMA XLT 15 is a high-performance, low-temperature Hydraulic Oil formulated using high-quality Group 3 base oils with anti-wear, oxidation and corrosion inhibitors and antifoam additives.

PEAK LOMA XLT 15 has been specially developed for medium to high pressure hydraulic systems operating in cool rooms or in cold climates where there is a wide variation in ambient temperature, such as in the construction, marine, mining and oil industries.

BENEFITS:

- · High viscosity index and a low pour point ensures excellent low-temperature fluidity and provides excellent low-temperature start up, protecting the hydraulic system from wear and extending component life.
- Excellent wear and corrosion protection, ensuring good equipment life and decreased downtime.
- Enhanced air release and anti-foam properties that prevent cavitation.
- Excellent filterability to prevent filter blockages delivering increased filter life and reduced maintenance
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and improved equipment performance.

| TFICAL CHARACTERISTICS . | | |
|---------------------------------|---------------|--|
| TEST | TYPICAL VALUE | |
| Density 15° C g/cm ³ | 0.834 | |
| Kinetic Viscosity @ 40°C cSt | 15.5 | |
| Kinetic Viscosity @ 100°C cSt | 3.8 | |
| Viscosity Index | 141 | |
| Pour Point °C | -45 | |
| Flash Point °C | >200 | |
| Colour | L 0.5 | |

ΤΥΡΙCΑΙ CHARACTERISTICS*

SPECIFICATIONS & PERFORMANCE LEVEL:

- Denison HF-0 / HF-1 / HF-2
- DIN 51 524 Part 3 (HLP type oils)

PRODUCT SIZES:

| PRODUCT CODE | PACK SIZE | CTN QTY |
|--------------|-----------|---------|
| PKIHH15LT020 | 20 Litre | |
| PKIHH15LT205 | 205 Litre | |

- Eaton Vickers 1-286-S, M-2950-S
 - US Steel 136 / 127

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 19 September 2022 * Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175 PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256 EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au



Proudly Australian Owned Since 1982

ABN: 74 8875 10101