



PEAK GLOBAL EXTREME 15W40

PREMIUM MINERAL DIESEL OIL

DESCRIPTION & APPLICATION:

PEAK GLOBAL EXTREME 15W40 Diesel engine oil is a heavy duty, low SAPS (Sulphated Ash, Phosphorus and Sulphur) product formulated for use in vehicles with or without Diesel Particulate Filters (DPF).

PEAK GLOBAL EXTREME 15W40 meets API CJ-4/SN, ACEA E9 making this suitable for diesel, LPG and petrol engines.

BENEFITS:

- Improved fuel efficiency
- Compliant with EPA emission requirements
- Excellent wear protection with long drain capability
- Great oxidation resistance to prolong lubricant life and prevent oil thickening

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.880
Viscosity 40°C cSt	120.6
Viscosity 100°C cSt	15.6
Viscosity Index	137.1
Flash Point °C	>210
Sulphated Ash	1.0
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDM1540GE020	20 Litre	
PKDM1540GE205	205 Litre	
PKDM1540GE1000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API CJ-4 / CI-4
- ✓ API SN
- ✓ ACEA E9/ E7
- ✓ Caterpillar ECF-3
- ✓ Cummins CES 20081 / 20076 / 20077
- ✓ Mack EO-M PLUS / EO-M
- ✓ Mack EO-N Premium Plus
- ✓ Volvo VDS-4 / VDS-3

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 9 February 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



**Proudly Australian Owned
Since 1982**