

PEAK AGRITRANS

MINERAL UTTO

DESCRIPTION & APPLICATION:

PEAK AGRITRANS is a multipurpose, 10W-30 UTTO (Universal Tractor & Transmission Oil) tractor transmission & hydraulic fluid manufactured using refined base oils and high-quality additive packages. PEAK AGRITRANS has been formulated specifically to suit a wide range of transmissions, hydraulics, PTOs, hydraulic bearings and some final drives fitted to tractors and construction equipment, especially those with wet brakes.

BENEFITS:

- Optimized frictional properties for brake chatter and brake capacity.
- Outstanding thermal and oxidation stability, non-foaming formulation.
- Protects against sludge and varnish formation through superior dispersion.

SPECIFICATIONS & PERFORMANCE LEVEL:

- | | |
|--|--|
| ✓ SAE 10W30 | ✓ New Holland 410B |
| ✓ ISO 68 (Hydraulic Oil) | ✓ AGCO Massey Ferguson CMS M1145 / M1143 / M1141 / M1135 |
| ✓ SAE 80 (Gear Oil) | ✓ AGCO Massey Ferguson White Q-1826 |
| ✓ API GL-4 | ✓ Volvo VCE WB 101 |
| ✓ Caterpillar TO-2 | ✓ ZF TE-ML-03E / 05F / 06E / 06F / 06K / 17E / 21F |
| ✓ John Deere JDM J20C/D (HyGard) | ✓ Eaton Vickers M-2950-S / 2952-S / 35VQ25 (pump stand) |
| ✓ Allis-Chalmers Power fluid PF-821 XL | ✓ FNHA-2-C-201 / 200A / 200 |
| ✓ Case New Holland 3525 (Multi G 134) / 3505 | ✓ MS 1209 (Hytrans Ultra & Multi Tran) / 1207 (Hytran Plus) / 1206 |
| ✓ Allison C-4 | |
| ✓ Kubota UDT / Super UDT | |
| ✓ JCMAS HK P-041 / P-042 | |
| ✓ Parker (Dension) HF-0 / 1 / 2 | |

PDS 14/07/2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982



PEAK AGRITRANS

MINERAL UTTO

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° Cg/cm ³	0.8592
Viscosity 40°C cSt	79.70
Viscosity 100°C cSt	11.86
Viscosity Index	147
Flash Point °C	>205
Colour	L 1.5

PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKG MAT005	5 Litre	4
PKG MAT020	20 Litre	
PKG MAT205	205 Litre	
PKG MAT1000	1000 Litre	

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982