



PEAK DRAWING OIL SSE

DRAWING AND STAMPING FLUID

DESCRIPTION & APPLICATION:

PEAK DRAWING OIL SSE is an extremely viscous extreme pressure concentrate based on a paraffinic hydrocarbon for use when drawing metals, particularly stainless steel; also for brushing on metal parts during machining operations

PEAK DRAWING OIL SSE is formulated to be water washable for easy "clean up". Water spray or water bath will emulsify Peak Drawing Oil SSE allowing for easy separation.

FEATURES & BENEFITS:

- Can be used neat for metal drawing, stamping and hand application for machining operations.
- Can be applied via both pumping and spraying.
- Outstanding performance with stainless steel and on brass

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	1.25
Kinetic Viscosity @ 40°C cSt	270
Active Ingredient	Chlorine

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKICMDSSE020	20 Litre	

APPLICATION :

- Use undiluted for metal drawing, stamping and hand application for machining operations.
- The product can be applied using a pump or spray.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 25 January 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982