



PEAK DRAWING OIL SSE

DRAWING AND STAMPING FLUID

PRODUCT DESCRIPTION

PEAK DRAWING OIL SSE is an extremely viscous extreme pressure concentrate based on a paraffinic hydrocarbon for use when drawing metals, particularly stainless steel; also for brushing on metal parts during machining operations.

PEAK DRAWING OIL SSE is formulated to be water washable for easy "clean up". Water spray or water bath will emulsify PEAK DRAWING OIL SSE allowing for easy separation.

SHELF LIFE: 12 months from the date of manufacturing

BENEFITS

- Can be used neat for metal drawing, stamping and hand application for machining operations
- Can be applied via both pumping and spraying
- Outstanding performance with stainless steel and on brass

APPLICATION

- Use undiluted for metal drawing, stamping and hand application for machining operations
- The product can be applied using a pump or spray

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm ³	0.96
Viscosity @ 40°C cSt	245
Active Ingredient	Chlorine

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKICMDSSE020	20 Litre		32
PKICMDSSE0205	205 Litre		4

PDS published on 09 Oct 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

<https://go.lupinsys.com/peaklubricants/harms/pm/ada520003a0d51c8ca6f719863526f59-published/attachment/sds.pdf>

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.

