

PEAK BLACK TACK GREASE

LITHIUM & 2% MOLYBDENUM DISULPHIDE GREASE NLGI 2

DESCRIPTION & APPLICATION:

PEAK Black Tack Grease is a premium, multipurpose lithium based NLGI 2 grease with Moly (Molybdenum Disulphide), suitable where shock load protection is required for automotive ball joints and constant velocity joints.

PEAK Black Tack Grease can also be used for plain and rolling element bearings, including heavily loaded bearings at low and medium speeds, and those subject to shock loading and excessive vibrations. It is also suitable for the lubrication of chains, swivels and shackles.

BENEFITS:

- High thermal and mechanical stability along with excellent resistance against rust and corrosion.
- Good load carrying capacity which protects equipment and reduces wear under extreme loading or shock loads.
- Excellent EP and anti-wear properties resulting in reduced bearing component wear.
- Good water resistance against water spray & washout.
- Strong adhesion between lubricated surfaces resulting in reduced consumption.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	2
Soap/Thickener Type	Lithium
Dropping point °C	195
Oil Viscosity 40°C cSt	150
4 Ball Weld Load, Kg	315
Operating Temperature Range °C	-20 to 130
Colour	Black

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXMOL450	450 G	
PKGXMOL02.5	2.5 KG	
PKGXMOL020	20 KG	
PKGXMOL055	55 KG	
PKGXMOL180	180 KG	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 8 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982