



PRODUCT DATA SHEET

PEAK SYN TORA 220

PAO SYNTHETIC INDUSTRIAL GEAR OIL

PRODUCT DESCRIPTION

PEAK SYN TORA 220 is a fully synthetic industrial gear oil which delivers outstanding performance under severe operating conditions such as high loads and wide temperature variations.

PEAK SYN TORA 220 is formulated using premium quality PAO (Poly Alpha Olefin Group IV) & ESTER (Group V) base oils which achieves optimal performance.

PEAK SYN TORA 220 has been specially developed to reduce friction and deliver long service life and to resist micro-pitting and maintain system efficiency.

BENEFITS

- Long service life reduces maintenance costs
- Excellent wear and corrosion protection
- High film strength for superior wear protection and load carrying capability even under shock loading conditions
- Outstanding flow properties over a wide temperature range enhances the efficiency of industrial gear systems

SPECIFICATIONS AND PERFORMANCE LEVEL

- US Steel 224
- DIN 51517-3 (CLP)
- Flender Rev 16
- AGMA 9005-F16
- David Brown S1.53.106
- SEB 181226

CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm ³	0.88
Viscosity @ 40°C cSt	212.2
Viscosity @ 100°C cSt	27.8
Viscosity Index	168
Flash Point °C	>210
Colour	L0.5

PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKIGF0220020	20 Litre		48
PKIGF0220205	205 Litre		4

PDS published on 23 May 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



Peak Lubricants Pty Ltd
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 | WEB: www.peakoil.com.au

