



# **PEAK ATF HV**

# **FULL SYNTHETIC TRANSMISSION FLUID**

# PRODUCT DESCRIPTION

PEAK ATF HV is a full synthetic high viscosity automatic transmission fluid suitable for use in 4, 5 & 6+ speed automatic transmissions in passenger cars, 4WD, light and heavy commercial vehicles.

PEAK ATF HV is formulated using a unique additive package and it meets most specifications recommended by original equipment manufacturers such as GM/Holden Dexron® IIIH, Ford Mercon® V, Nissan Matic W, Mitsubishi SP-II / SP-III, Chrysler / Dodge / Jeep ATF+3 / ATF+4 and many more.

#### **BENEFITS**

- · Superior anti-shudder durability performance
- · High torque holding capacity
- · Excellent shift feel durability performance
- · Improved power transfer and fuel economy

### SPECIFICATIONS AND PERFORMANCE LEVEL

- Allison C4 / TES-295® / TES-389®
- GM/Holden Dexron® IIIH
- MAN 339A
- Ford Mercon® V
- Ford WSS-M2C922-A
- · Hyundai/Kia SP-III
- Mazda F-1
- MB 236.91 / 236.9 / 236.8 / 236.7 / 236.6
  / 236.5 / 236.3 / 236.15 / 236.11 / 236.10
- SsangYong DSIH 5M-66

- Chrysler ATF+3 / ATF+4
- JASO 1A
- Nissan Matic W / K / J / D
- Honda ATF-Z1
- Jeep SP-III
- Subaru HP
- Renaultmatic D2
- VW/Audi AG G 052 025 A2 / G 052 055 / G 052 162 A1
  / G 052 162 A2 / G 052 990 A2 / G 055 025 A2
- Volvo Construction Equipment 1273.41

# **CHARACTERISTICS**

Test Typical Va		
Density 15° C g/cm³	0.848	
Viscosity @ 40°C cSt	35.4	
Viscosity @ 100°C cSt	6.9	
Viscosity Index	156	
Flash Point °C	>205	
Colour	Red	

# **PRODUCT SIZE**

Part Number	Size	Carton Qty	Pallet Qty
PKTFHV005	5 Litre	4	192
PKTFHV020	20 Litre		48
PKTFHV205	205 Litre		4

PDS published on 19 Mar 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



