



## PRODUCT DATA SHEET

# PEAK ATF DX3

## PREMIUM MINERAL TRANSMISSION FLUID

### PRODUCT DESCRIPTION

PEAK ATF DX3 is formulated premium mineral based oil combined with the highest quality additives in order to satisfy the latest transmission designs.

PEAK ATF DX3 is designed for use in passenger cars, 4WD's and light commercial vehicles where GM Dexron® III and Ford Mercon® fluids have been specified. The improved low-temperature properties and excellent retention of frictional coefficient ensure consistently smooth shifts, both at a cold start and under extreme operating conditions, it also suitable for hydrostatic transmissions, power steering systems, and hydraulic systems.

### BENEFITS

- Low pour point, no foaming
- High thermal stability
- Safe friction coefficient characteristics

### SPECIFICATIONS AND PERFORMANCE LEVEL

- Allison C4 / TES-389B®
- GM Dexron® II / Dexron® III G
- Mitsubishi DiaQueen SP-II
- Ford Mercon®
- Ford WSS-M2C166-H
- Voith 55.6335
- ZF TE-ML 05L / TE-ML 09L
- BTR M95LE / M85LE
- Hyundai/Kia SP-II
- MB 236.7 / 236.5 / 236.2 / 236.1

### CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm³	0.858
Viscosity @ 40°C cSt	40.3
Viscosity @ 100°C cSt	7.6
Viscosity Index	158
Flash Point °C	>210
Colour	Red

### PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKTMD3001	1 Litre	6	780
PKTMD3005	5 Litre	4	192
PKTMD3020	20 Litre		32
PKTMD3060	60 Litre		9
PKTMD3205	205 Litre		4
PKTMD31000	1000 Litre		

PDS published on 07 Jul 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.



**Peak Lubricants Pty Ltd**  
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175  
PHONE: 03 9799 0977 | WEB: [www.peakoil.com.au](http://www.peakoil.com.au)

